

GAMUL
powered by LUMAG

T8

Vertical Hydraulic - Log Splitter

PRODUKT-INFORMATION

Technical Data

GAMUL T8

Current power	230 V / 50 Hz
Motor power	3,0 kW
Operating mode	S6 40%
Protection class	IP54
Motor speed	2800 min ⁻¹
Motor protection	Yes
Phase inverter	No
Splitting force	8t
Splitting diameter	80 – 300 mm
Splitting length	250 – 520 mm
Hydraulic oil volume	max. 3,3 Liter (HLP46)
Hydraulic pressure	22,0 MPa
Delivery capacity	4,2 l/min
Working speed	ca. 3,1 cm/s
Reverse speed	ca. 15,0 cm/s
Dimensions (LxWxH)	880x600x1020 mm
Splitting wedge retracted	
Dimensions (LxWxH)	880x600x1490 mm
Splitting wedge raised	
Weight (net / gross)	89,5 / 93 kg
Packaging dimensions (LxWxH)	570x420x1045 (1165) mm



Art. Nr. GAMULT8

EAN: 40 47424 00896 6



Equipment Features:

- Complies with the latest safety standards
- Compact vertical design for splitting hard and soft wood up to max. 520 mm
- Torsion-resistant, power-coated steel construction ensure high stability
- High-quality hydraulic pump with powerful 230V motor
- Optimal safety due to 2-hand operation and access protection
- Shelf on both sides for split wood
- Standard equipment with transport device and transport handle